



# AGS 2+ GEL

ART. NO: 3640 | GRAFFITI REMOVER

**AGS 2+ GEL** is a powerful graffiti and paint remover. For use on exterior and interior surfaces. **AGS 2+ GEL** may be used on porous surfaces. Readily biodegradable according to OECD test 302 B.

**AGS 2+ GEL** is a thickened, highly effective graffiti remover for use on porous and some hard surfaces.

**AGS 2+ GEL** effectively dissolves spray paint graffiti and permanent markers.

**AGS 2+ GEL** may be used on following surfaces:

Porous surfaces: Concrete, brick, granite, marble, limestone, sandstone, slate, surfaces painted with non-organic paint.

Hard surfaces: Metal, treated wood, clinker, glazed brick, glass.

## INSTRUCTIONS FOR USE

Apply **AGS 2+ GEL** with a brush or airless sprayer. Agitate the surface well. Leave until graffiti has dissolved, 20 minutes – 4 hours. In cold weather, the time increases. Jet off with hot water and high pressure, (90°C, 150 bar/2175 PSI). Lance nozzle spread should be 15 - 25 degrees and water flow should be 15 to 20 litres/minute, (4-5 gal/minute). If pigment shadows remain, use [AGS 60](#) or [AGS 65](#).

**NB!** For metal surfaces do not use too high pressure. Instead wipe with sponge or cloth and rinse with warm water.

## Dosage

Use as concentrate.

## Consumption

0,5 - 1,0 ltr/m<sup>2</sup>.

## Storage

Store frost-free in original closed container.

## Shelf life

Approximately 24 months in unopened container.

## Precautions

Use protective gloves, clothing and glasses.

## Technical data

- Viscous yellowish fluid.
- Packaging: 5 or 25 litre plastic jerricans.
- Density: 1,09 kg/ltr.
- Mild odour.
- Flash point 106 °C
- Contains: 1-butylpyrrolidin-2-one, 1-methoxypropanol.

## Marking

Warning



Harmful if swallowed. Causes skin irritation. Causes serious eye irritation.

Not classified as dangerous goods according to **ADR**. For more information, see [MSDS](#).

Modified: 2023-06-13

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and are responsible for the result.