



Svederusgatan 1-3, SE-754 50 Uppsala, Sweden. Tel: +46 18-15 61 90.

email: info@trion.se. www.trion.se



AGS 3+ GEL ART. NO: 3650 | GRAFFITI REMOVER

AGS 3+ GEL is a powerful graffiti and paint remover. For use on exterior and interior surfaces. AGS 3+ GEL may be used on porous surfaces. Readily biodegradable.

AGS 3+ GEL is a thickened highly effective graffiti remover to be used on both porous and hard surfaces.

AGS 3+ GEL dissolves spray-paint graffiti, permanent markers and even petroleum based rust protective sealers. AGS 3+ GEL may be used on following surfaces:

Porous surfaces: Concrete, brick, granite, marble, limestone, sandstone, slate, surfaces painted with nonorganic paint.

Hard surfaces: Metal, treated wood, clinker, glazed brick, glass.

INSTRUCTIONS FOR USE

Apply AGS 3+ GEL with a brush or airless sprayer. Agitate the surface well. Leave until graffiti has dissolved, 20 minutes - 4 hours. In cold weather, the time increases. Jet off with hot water and high pressure, (90°C, 150 bar/2175 PSI). Lance nozzle spread should be 15 - 25 degrees and water flow should be 15 to 20 litres/minute, (4-5 gal/ minute). If pigment shadows remain, use AGS 60 or AGS 65.

NB! For metal surfaces do not use to high pressure. Instead wipe with sponge or cloth and rinse with warm water.

Dosage

Use as concentrate.

Consumption

0,5 - 1,0 ltr/m².

Storage

Store frost-free in original closed container.

Approximately 24 months in unopened container.

Precautions

Use protective gloves, clothing and glasses.

Technical data

- Viscous bluish fluid.
- Packaging: 5 or 25 litre plastic jerricans.
- Density: 0,98 kg/litre.
- Contains benzyl alcohol, 1-methoxypropanol.

Marking

Warning



Harmful if swallowed or inhaled. Causes skin irritation. Causes serious eye irritation.

Not classified as dangerous goods according to ADR. For more information, see MSDS.