

Svederusgatan 1-3, 754 50 Uppsala, Sweden. Tel: 018-15 61 90.

email: info@trion.se. www.trion.se



AGS 60

ART. NO: 3660 | SHADOW REMOVER

AGS 60 is used for removal of graffiti-shadows in conjunction with graffiti removal. Readily biodegradable according to OECD test 302 b. For use on exterior and interior surfaces. Primarily used on absorbent surfaces.

AGS 60 removes shadowing left on surfaces following graffiti removal, in special cases also paint removal.

AGS 60 is formulated for use on the following materials: granite, slate, sandstone, glazed brick, treated marble, wood and non-organic paint.

NB! Do not use AGS 60 on soft metals as aluminium.

INSTRUCTIONS FOR USE

Graffiti-shadow removal

Apply **AGS 60** with a brush on wet surface, leave to act for 2 - 30 minutes until graffiti/shadowing has dissolved. Jet off with high-pressure hot water, (40-90°C, 70-150 bar/1015-2175 PSI). Adjust pressure to suit surface condition.

NB! For metal surfaces, the effectiveness can be reduced if the pressure is too high. A better result can be achieved if the surface is wiped with a sponge or cloth in the rinsing process. Repeat the procedure if required.

Dosage

Use as concentrate.

Consumption

0,2 - 0,5 litre/m² per application using concentrate.

Storage

Store frost-free in closed original container.

Shelf life

Approximately 24 months in unopened container.

Precautions

Special caution must be taken, as **AGS 60** is a **CORROSIVE** product. Use protective gloves, clothing, and glasses If product comes in contact with eyes, rinse with lot of water and immediately go to hospital. If in contact with the skin, rinse with lot of water, go to hospital if necessary.

Technical data

- Brownish slight viscous fluid.
- Packaging: 5 or 25 litre plastic jerricans.
- Density: 1,08 kg/lt.
- pH-value approx. 14.
- Flash point: >67°C
- Contains Potassium hydroxide, 2-Butoxyethanole, 1-methoxypropanol.

Marking



Harmful if swallowed. Causes severe skin burns and eye damage.

Classified as dangerous goods according to ADR.

UN 1814, POTASSIUM HYDROXIDE SOLUTION

Class: 8 PG: II

For more information, see MSDS.