

BPS 7624 GEL

ART. NO: 7624 | PAINT REMOVER

BPS 7624 GEL is a biodegradable and user friendly paint remover for surfaces painted with both latex and solvent based paint. Removes old paint that have been aged. Removes several layers in one application. Clings to vertical surfaces.

BPS 7624 GEL is an environmentally friendly and easy to use paint remover for both latex and solvent based paint. Can be used on most surfaces such as concrete, glass, tiles, metal, mineral surfaces, plaster, bricks and wood. Thickened so it clings on the surface for a long time. **BPS 7624 GEL** have a long open time, i.e. it can dwell on the surface for a long time without drying out.

Instructions for use

Surfaces that shall not be treated should be covered, protect sensitive vegetation and fence off the work area. Apply **BPS 7624** with a brush, roller or spray gun. The gaskets in the spray gun has to withstand solvents. Allow to dwell on the surface for 1-36 hours, the time depends on the temperature, the age of the paint, the paint thickness, and the surface structure. The dissolved paint can be scraped off or is jetted off with high pressure and hot water. (Pressure depending on surface, 50-300 bar/ 20 litre/ min., 25-45° angle nozzle, 90°C gives the best effect). Work from bottom to the top. Angel the high pressure nozzle so the water is sprayed on surfaces where the paint has already been removed.

NB! Avoid to spray water on surfaces where **BPS 7624 GEL** is dissolving paint. When the surface is cleaned, rinse off with low pressure from top to bottom. If **BPS 7624 GEL** is used to remove paint from a roof it is recommended that the dissolved paint is scraped off into a container and then jet off with high pressure.

Environmental aspects.

BPS 7624 GEL is biodegradable, but before the dissolved paint is rinsed off it is recommended to check the local regulations with the local authorities. The dissolved paint may be subject to local environmental regulations.

Dosage

Use as concentrate.

Consumption

The consumption is depending on surface structure, thickness of paint and number of layers. Normal usage is approximately 0,5- 2.0 litre/m².

Storage

Store frost-free in original container.

Shelf life

24 months in unopened container.

Precautions

Use protective gloves, clothes and glasses.

Modified: 2023-06-13

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and are responsible for the result.

Technical data

- Viscous yellowish liquid with a solvent odour.
- Packaging: 10 litre plastic jerricans or 20 litre plastic buckets.
- Density: 0,97 kg/litre.
- Flash point >70 °C.
- Contains benzyl alcohol, 1-methoxypropanol.

Marking

Warning



Harmful if swallowed or if inhaled. Causes skin irritation.
Causes serious eye irritation.

Not classified as dangerous goods according to **ADR**.
For more information, see [MSDS](#).

Modified: 2023-06-13

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and are responsible for the result.